















Suspended decorative luminaire for LED light sources.

TECHNICAL DATA **Mounting:** suspended, on wire suspension (included) $\textbf{Body:} \ top\ quality\ aluminum\ powder\ painted\ ecru\ and\ black$

Colour: ecru

ELECTRICAL DATA Power: 220-240V 50/60Hz

Includes light source: yes Type of equipment: ED

OPTICAL DATA Way of lighting: direct ADDITIONAL INFO Available on request: DALI

Other remarks: for metal halide version - please order MH light sources

GENERAL DATA Warranty: 3 years + 2 years after project registration


Application: offices, conference rooms, reception desks, shopping centers, car


rooms, boutiques




Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
210060.5L01.11	24	17,5	21	1560	1560	74	4000	92
210060.5L02.11	24	17,5	21	1430	1430	68	3000	92
210060.5L03.11	40	17,5	21	1560	1560	74	4000	92
210060.5L04.11	40	17.5	21	1430	1430	68	3000	92

	Code	Dimensions [mm] L W H	Mounting dimensions [mm] D	Pallet quantity	Quantity in package	Net weight [kg]
	210060.5L01.11	180 180 200	100	96	1	3.5
	210060.5L02.11	180 180 200	100	96	1	3.5
	210060.5L03.11	180 180 200	100	96	1	3.5
	210060.5L04.11	180 180 200	100	96	1	3.5







OTHER PICTURES



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.
Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.
Up-to-date product info available on our website www.flashdq.com

Date of issue:

26-2-2016





LIGHT BEAM CURVES

